ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL Manual No.: Procedure No.: 5-21000-OPS-GT

Table of Contents, Rev 11

1 of 3

Page: Effective Date:

12/20/91

Organization:

**Environmental Management** 

## THIS IS ONE VOLUME OF A SIX VOLUME SET WHICH INCLUDES:

**VOLUME I: FIELD OPERATIONS (FO) VOLUME II: GROUNDWATER (GW)** VOLUME III: GEOTECHNICAL (GT)

CONTROLLED SOCUMATINE IV: SURFACE WATER (SW) EG&G - ROCKY FLATS PLANT

**VOLUME V: ECOLOGY (EE)** 

ENVIRONMENTAL MANAGEMENT DEPARTMENT

This is a RED Stamp

TABLE OF CONTENTS

FOR VOLUME III: GEOTECHNICAL

Proc. <u>No.</u>	Title	Rev. <u>No.</u>	Effective <u>Date</u>
GT.01	Logging Alluvial and Bedrock Material	1	08/30/91
DCN 91.01	Recording lithologic descriptions and securing core boxes	1	11/15/91
DCN 91.02	Clarification of log approval for multi-use wells	1	12/03/91
GT.02	Drilling and Sampling Using Hollow Stem Auger Techniques	1	08/30/91
DCN 91.01	Unconsolidated core samples need not be peeled before sampling	1 ,	10/29/91
DCN 91.02	Correction of well location for low Alluvial thickness	1	11/06/91
DCN 91.03	Ten foot long core barrels	1	11/15/91
GT.03	Isolating Bedrock from Alluvium with Grouted Surface Casing	1	08/30/91
DCN 91.01	Superseded by DCN 91.03	1	10/02/91
DCN 91.02	Grout procedure clarification	1	10/28/91
DCN 91.03	Change in criteria for cement grouting	1	12/12/91

REVIEWED FOR CLASSIFICATION/UCNI. 1-6-05 - <sub>A-SW-001098</sub>

**ADMIN RECORD** 

ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL

Manual No.: Procedure No.: Page: Effective Date: 5-21000-OPS-GT Table of Contents, Rev 11 2 of 3

12/20/91

Organization: Environmental Management

Proc. No.	<u>Title</u>	Rev. <u>No.</u>	Effective <u>Date</u>
DCN 91.04	Depth of casing emplacement	1	12/17/91
DCN 91.05	Addition of Grout Ports	1	12/19/91
GT.04	Rotary Drilling and Rock Coring	1	08/30/91
DCN 91.01	Core barrel decontamination	1	10/22/91
DCN 91.02	Clarification of measuring tape decontamination requirements	1	10/29/91
DCN 91.03	Superseded by DCN 91.04	1	12/03/91
DCN 91.04	Clarification of the use of super gel-x	1 .	12/17/91
GT.05	Plugging and Abandonment of Boreholes	1	08/30/91
DCN 91.01	Surface casing classification	1	10/22/91
GT.06	Monitoring Wells and Piezometer Installation	1	08/30/91
DCN 91.01	Industry Standard is 1 foot into Bedrock	1	10/15/91
DCN 91.02	For the Sitewide Program, Claystone Smearing does not seem to be a problem	1	10/15/91
DCN 91.03	Superseded by DCN 91.06	1	11/08/91
DCN 91.04	Low Alluvial thickness wells	1	11/06/91
DCN 91.05	Superseded by DCN 91.08	1	11/06/91
DCN 91.06	Change in filter pack guidance	1	11/08/91
DCN 91.07	Decontamination for site-wide geological chracterization	1	11/15/91
DCN 91.08	Figure replacement (GT.6-1)	1	11/15/91
DCN 91.09	Sampling with center bit drilling	1	12/03/91

ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL

Manual No.: Procedure No.: 5-21000-OPS-GT Table of Contents, Rev 11

Page:

3 of 3

Effective Date:

12/20/91

Organization:

**Environmental Management** 

Proc. No.	r. <u>Title</u>		Effective Date
GT.07	Logging and Sampling of Test Pits and Trenches	1	8/30/91
GT.08	Surface Soil Sampling	1	8/30/91
DCN 91.01	Clarification supplementation of GT.08 - Surface Soil Sampling	1	11/26/91
GT.09	Soil Gas Sampling and Field Analysis	1	8/30/91
GT.10	Borehole Clearing	1	8/30/91
GT.11	Plugging and Abandonment of Wells	1	8/30/91
GT.15	Geophysical Borehole Logging	1	8/30/91
DCN 91.01	No Hole will be left Unlogged at the end of the day	1	10/15/91
GT.17	Land Surveying	1	8/30/91
GT.18	Surface Geophysical Surveys	1	8/30/91
GT.19	Field Gas Chromatographs	1	8/30/91
GT.20	Procedures for Soil Interstitial Water Sampling and Sampler Installation	1	8/30/91

## ENVIRONMENTAL MANAGEMENT DOCUMENT CHANGE NOTICE (DCN)

Procedure Number 5-21000-OPS-GT.3 Rev. 1

Page 1 of 1

Title Isolating	Bedroc	k from Alluvius	m with Groute	d Suriace Ca	1	Date 12-16-91	DCN Nun 5-21000-	nber OPS-G-T, J
Expires Scope Lin	3//	7/9/2 none	P	rocedure Rev	vision Required	X Yes No		
ltem Number	1 1							
paragraph 2 Replace the last two sentences with: "Based on field expenence at RFP, casing may be emplaced to depths of up to in highly weathered or iractured bedrock to ensure a good seal."					up to 60 feet			
			This is a  CONTROLLED DOCUMENT  EGSG — ROCKY FLATS PLANT  ENVIRONMENTAL MANAGEMENT DEPARTMENT  This is a RED Stamp					
		·						
Savere we surface ca	athering sing is er	and fracturing	, have been e	ncountered i	n many of the bo	anding items Above reholes to depths of tally broken allowing	: 40 to 50 (e	et. When ids to circulate
Concurre	i	Organizatio	n Req	Date	Concurrence	Organization	Req	Date
4/-	XV4	QAPM	X	12/17/-	12 Lemo	Liser	X	12/10/91
M.C.B.	enstand.	Еом	×	ishu fa:				
opproval of	Respon	sible Manager	Date 12/16/	(9)	Is Posting Requ	if Yes. By What	Date?	Date Posted